

# BB115

# ULTRABASS

## Technical Specifications

Version 1.1 September 2004

ENGLISH



[www.behringer.com](http://www.behringer.com)



# ULTRABASS

**High-Performance 600-Watt Bass Cabinet with an Original 15" BUGERA™ Speakers and 1" Horn Driver**

- ▲ Reinforced chamber, front-ported bass cabinet for 600 Watts of power handling
- ▲ Original BUGERA™ speakers with special high-impact cones
- ▲ Powerful and punchy bass tone
- ▲ Switchable 1" custom-made horn tweeter for high-end punch
- ▲ Unique tweeter remote control via footswitch or BEHRINGER MIDI FOOT CONTROLLER FCB1010
- ▲ Input and link outputs on 1/4" TS and professional speaker connectors (compatible with NEUTRIK® SPEAKON®), impedance 8 Ohms
- ▲ Recessed carrying handles and integrated rollers for easy transportation
- ▲ Shock proof metal grille, reinforced corners and rugged carpet covering
- ▲ Exceptionally rugged construction for long life and durability
- ▲ Conceived and designed by BEHRINGER Germany



## SPECIFICATIONS

### SPEAKERS

High-power bass speakers	15" BUGERA™
Sensitivity	96 dB @ 1 W / 1 m
Impedance	8 Ohm
Frequency response	38 Hz - 16 kHz
Power (RMS / Music)	600 W
Tweeter	1" tweeter driver

### SPEAKER CONNECTIONS

Input/Link	2 professional speaker connectors, compatible with NEUTRIK® SPEAKON® (wired in parallel) as well as one 1/4" connector
TS	

### DIMENSIONS/WEIGHT

Dimensions (H x W x D)	655 mm x 655 mm x 366 mm (25 4/5" x 25 4/5" x 14 2/5")
Weight	ca. 32.0 kg (70.6 lb)

Technical specifications and appearance subject to change without notice. The information contained herein is correct at the time of printing. NEUTRIK®, SPEAKON® as well as the names of companies, institutions or publications pictured or mentioned and their respective logos are registered trademarks of their respective owners. Their use neither constitutes a claim of the trademarks by BEHRINGER® nor affiliation of the trademark owners with BEHRINGER®. BEHRINGER® accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colours and specification may vary slightly from product. Products are sold through our authorised dealers only. Distributors and dealers are not agents of BEHRINGER® and have absolutely no authority to bind BEHRINGER® by any express or implied undertaking or representation. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studioteknik GmbH. BEHRINGER® is a registered trademark.

ALL RIGHTS RESERVED. © 2004 BEHRINGER Spezielle Studioteknik GmbH.  
BEHRINGER Spezielle Studioteknik GmbH, Hanns-Martin-Schleyer-Str. 36-38,  
47877 Willich-Münchheide II, Germany  
Tel. +49 2154 9206 0, Fax +49 2154 9206 4903