en

Technical Specifications

Version 1   2007-06

www.behringer.com

BEHR**ING**ER

JUST LISTEN.

B-CONTROL ▶*FADER*

Total Recall USB/MIDI Controller Desk with 8 Motorized Faders

en

▲ Unique, total recall cascadable desktop MIDI controller with analog feel and an intuitive user interface

▲ 8 ultra-precise 100-mm motorized faders for ultimate control of virtual mixers, organ-drawbars (inverse mode) or virtual synths and samplers

▲ 4 virtual groups with 8 dual-mode, high-resolution encoders that feature LED rings and an additional push function

▲ 16 + 4 illuminated buttons freely assignable to all types of MIDI functions from note on/off, control change and program change to MMC and system exclusive data

▲ All panel elements freely assignable—manually or via user-friendly learn mode

▲ Additional multi-function foot switch and foot controller connectors can be used to address all types of MIDI data

▲ 32 user presets each with 4 encoder groups

▲ Configurable MIDI and USB modes for ultra-flexible system integration

▲ 1 MIDI In plus 2 MIDI Outs, usable as an additional USB to MIDI interface

▲ Multi-function 4-digit LED display with real-time parameter indication plus write-in fields for your own labeling

▲ MIDI input with merge function for cascading several control units

▲ Easy connection to any computer/expander, etc. using standard MIDI In/Out connectors

▲ Generic USB MIDI support with Windows XP and Mac OS X operating systems

▲ Additional drivers and editor/librarian software available for free download on our website

▲ High-quality components and exceptionally rugged construction for long life and durability

▲ Conceived and designed by BEHRINGER Germany

SPECIFICATIONS

USB INTERFACE
Type   Full-speed 12 MBit/sec.
       USB MIDI class-compliant

MIDI INTERFACE
Type   5-pin DIN connectors IN, OUT A,
       OUT B/THRU

CONTROL ELEMENTS
Controls   8 motorized 100-mm faders
       8 infinitely variable push encoders
       with LED rings
Keys   20 keys
       10 system keys (4x Encoder Group,
       4x programming, 2x Preset)

DISPLAY
Type   4-digit 7-segment LED display

SWITCHED INPUTS
Footswitch   1 x ¼" TS connector
       with automatic polarity detection
Foot pedal   1 x ¼" TRS connector

POWER SUPPLY
Voltage   100 to 240 V~, 50/60 Hz
Power consumption max. 15 W
Fuse   **T 1 A H** 250 V
Mains connection Standard IEC receptacle

DIMENSIONS/WEIGHT
Dimensions
(W x H x D)   13" x 4" x 11 4/5"
       (330 mm x 100 mm x 300 mm)
Weight   approx. 2,60 kg (5 ¾ lbs.)

en

BEHRINGER is constantly striving to manintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.