



Technical Specifications



MINIFEX FEX800

Ultra-Compact Stereo Multi-FX Processor

MINIFEX FEX800

Ultra-Compact Stereo Multi-FX Processor

- Ultra-compact stereo multi-effects processor for podcast, studio and stage applications
- 16 awesome FX presets in 24-bit resolution including reverb, delay, chorus, flanger, phaser, rotary speaker, pitch shifter and multi-effects
- Intuitive FX Preset control with LEDs indicating the selected program
- Versatile Edit and Tap/Select functions to control a wide range of FX parameters
- Stereo Input Level control with accurate 6-segment LED Input meter for precise level indication
- Dedicated Mix Balance and Output Level controls for perfect effects level adjustment
- Additional footswitch connector for easy FX on/off control
- All Mini Series models can be stacked on top of each other to create an ultra-compact signal processor solution
- High-quality components and exceptionally rugged construction ensure long life
- Conceived and designed by BEHRINGER Germany

Specifications

Input		System Specifications	
Type	¼" TS connectors, unbalanced	Frequency response	10 Hz to 22 kHz, -3 dB
Impedance	approx. 30 kΩ	Dynamic range	96 dB, 10 Hz to 22 kHz
Output		Distortion	0,01% typ. @ 0 dBFS
Type	¼" TRS connectors, impedance balanced	Crosstalk	-75 dB @ 1 kHz
Impedance	approx. 220 Ω	Signal-to-noise ratio	10 Hz to 22 kHz <86 dB @ 0 dBu, A-weighted
Max. output level	+10 dBu	Power Supply	
In/Out		Mains connection	external power supply, 9 V~, 750 mA
Type	¼" TS footswitch connector	Mains Voltage	
Digital Processing		USA/Canada	120 V~, 60 Hz
Converters	24-Bit Delta-Sigma, 128-times oversampling	U.K./Australia	240 V~, 50 Hz
Sampling rate	48 kHz	China	220 V~, 50 Hz
		Europe	230 V~, 50 Hz
		Japan	100 V~, 50 - 60 Hz
		Power consumption	approx. 7.5 W
		Dimensions/Weight	
		Dimensions (H x W x D)	approx. 1.9 x 4.7 x 9.6" approx. 48 x 120 x 242.6 mm
		Weight	approx. 1.46 lbs / 0.66 kg

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

TECHNICAL SPECIFICATIONS AND APPEARANCE ARE SUBJECT TO CHANGE WITHOUT NOTICE. THE INFORMATION CONTAINED HEREIN IS CORRECT AT THE TIME OF PRINTING. ALL TRADEMARKS ARE THE PROPERTY OF THEIR RESPECTIVE OWNERS. MUSIC GROUP ACCEPTS NO LIABILITY FOR ANY LOSS WHICH MAY BE SUFFERED BY ANY PERSON WHO RELIES EITHER WHOLLY OR IN PART UPON ANY DESCRIPTION, PHOTOGRAPH OR STATEMENT CONTAINED HEREIN. COLORS AND SPECIFICATIONS MAY VARY FROM ACTUAL PRODUCT. MUSIC GROUP PRODUCTS ARE SOLD THROUGH AUTHORIZED FULLFILLERS AND RESELLERS ONLY. FULLFILLERS AND RESELLERS ARE NOT AGENTS OF MUSIC GROUP AND HAVE ABSOLUTELY NO AUTHORITY TO BIND MUSIC GROUP BY ANY EXPRESS OR IMPLIED UNDERTAKING OR REPRESENTATION. THIS MANUAL IS COPYRIGHTED. NO PART OF THIS MANUAL MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING AND RECORDING OF ANY KIND, FOR ANY PURPOSE, WITHOUT THE EXPRESS WRITTEN PERMISSION OF MUSIC GROUP IP LTD. ALL RIGHTS RESERVED. © 2011 MUSIC GROUP IP LTD. TRIDENT CHAMBERS, WICKHAMS CAY, P.O. BOX 146, ROAD TOWN, TORTOLA, BRITISH VIRGIN ISLANDS