



Coliseum Mini Installation Series

C120

Overview

The Coliseum C120 is a high-end, water resistant speaker featuring specially treated drivers and a sculpted ABS plastic enclosure. This compact speaker is ideally suited for many applications: commercial installations, home theatre, home stereo, mobile applications, reference monitor, personal stage monitor and can even be used outdoors.

The C120 is a bass reflex enclosure with a tuned port and a 5" woofer, which provides improved bass performance over conventional 5" woofer enclosures. Removing the press-fit grille gives access to the eyeball tweeter, which can be swiveled to suit various listening positions. The C120 will handle 100 Watts of continuous music and is accurate from 75 Hz to over 19 kHz.

The C120 is designed to allow a multitude of mounting options including a 'press-fit' microphone stand mount, integral key hole screw-slots or the provided metal U-bracket which allows it to be angled up, down or sideways depending on the mounting orientation. For maximum convenience in live or mobile applications, the back plate features push terminals and dual 1/4" inputs. The C120 is available in a low-reflectance black (C120) or white (C120W) finish with a matching, perforated metal grille and can be painted to match its surroundings.

Also available is the C120/70. The integrated 70V 'matching transformer' allows multiple C120/70's to be connected together without danger of overloading the power amplifier due to impedance drop. The user has a choice of three sensitivity settings (10W, 20W, 30W or bypass) selected via a rotary switch located on the rear panel of the speaker, allowing convenient adjustment of the relative volumes of multiple interconnected cabinets.

The C120 is available in both black (C120) and white (C120W) finishes.



Features

- 100 watt / 8-ohm Bass Reflex Two-Way Installation Loudspeaker
- 5-inch Woofer / Aimable Swivel 1-inch Mylar Tweeter
- 1/4-inch and Push Terminal Inputs
- ABS Plastic Cabinet and Metal Grille
- Mounting U-Bracket Included
- Available in White (C120W) or Black (C120) Finishes



Specifications

System Type	2-way
Active or Passive	Passive
Program Power (Watts)	100
Nominal Impedance (Ohms)	8
Sensitivity (dB @1Watt/1m)	94
Max SPL (dB)	104
Frequency Response (Hz +/- 3dB)	75 - 19,000
Driver Configuration	Tweeter, 5 inch
HF Driver(s)	Aimable Mylar Tweeter
HF Dispersion (°H x °V)	90 x 90
LF Driver(s)	5 inch
Inputs	3
Inputs - 1/4" Jacks	2
Inputs - Screw Terminal	1 (Push Terminal)
Flying Hardware	U-Bracket, 2 Rear Key Hole Mounts, Mic Stand Mount
Optional Flying Hardware	No
Enclosure Materials	Injection Molded, ABS Plastic
Port(s)	1
Grille	Perforated Steel
Covering / Finish	Low Reflective Black (C120)
Optional Covering / Finishes	Low Reflective White (C120W)
Dimensions (DWH xbackW, inches)	6.5 x 6.75 x 10.25 x 6
Dimensions (DWH xbackW, cm)	16.5 x 17 x 26 x 16
Weight (lbs/kg)	4.7 / 2.1

Specifications subject to change without notice